



IS 130C



IS 50C/120C



IS 80P

INDUCTION SEALERS

Induction sealers are used for hermetically sealing the plastic & glass bottle caps with aluminum foils. This makes the bottles leak- proof & tamper evident and offers extended shelf life. Induction sealers are widely used in Pharmaceutical, Chemical, Lubricant, Cosmetic and Food industries.

TECHNICAL SPECIFICATIONS

| IS 130C | | IS 50C | | IS 120C | |
|-----------------|----------------------|----------------|----------------------|----------------|----------------------|
| Power | 2 KW@ 240 V 50Hz | Power: | 1.5 KW@ 240 V 50Hz | Power | 2 KW@ 240 V 50Hz |
| Conveyor speed | 0~ 12 Mts./Min. | Conveyor speed | 0~ 10 Mts./Min. | Conveyor speed | 0~ 10 Mts./Min. |
| Bottle Dia | 30 ~ 130 mm | Bottle Dia | 20 ~ 50 mm | Bottle Dia | 30 ~ 120 mm |
| Bottle Height | 40 ~ 300 mm | Bottle Height | 40 ~ 200 mm | Bottle Height | 40 ~ 400 mm |
| Dimensions (mm) | 1550 x 580 x 1430 | Size (mm) | 1170 x 490 x 640 | Size (mm) | 1170 X 610 X 655 |
| Weight | 72 Kgs. | Weight | 38 Kgs. | Weight | 40 Kgs. |
| Sealing Speed | up to 20 bottles/min | Sealing Speed | up to 20 bottles/min | Sealing Speed | up to 20 bottles/min |

PORTABLE

*Sealing speed depending on bottle size

| Parameter | IS 80P | IS 120P |
|-----------------------------|-----------------|-----------------|
| Supply | 240VAC / 50Hz | 240VAC / 50Hz |
| Power Consumption | 500W | 1000W |
| Dimension (mm) | 345 x 330 x 145 | 345 x 330 x 145 |
| Weight | 3.5Kg | 3.6Kg |
| Sealing Head Dimension (mm) | 115 x 190 | 158 x 190 |
| Bottle Dia (mm) | 20 to 80 | 40 to 120 |